L Number	Hits	Search Text	DB	Time stamp
1	1076	generate with (SQL "structured query languate")	USPAT; US-PGPUB; EPO; JPO	2004/05/12 09:51
2	684	generate with (SQL "structured query languate") and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/12 09:54
3	63	generate with (SQL "structured query languate") with function and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:01
4	0	generate with (SQL "structured query languate") with statement and convert with text with format and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:02
5	1	generate with (SQL "structured query languate") with statement and convert with string with (format type) and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:50
6	2	build$4 with function with exist with database	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:58
7	8207	generate with exist	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:59
8	240	generate with exist with function	USPAT; US-PGPUB; EPO; JPO	2004/05/12 10:59
9	1	generate with exist with function with parse	USPAT; US-PGPUB; EPO; JPO	2004/05/12 11:00
10	4	generate with exist with function with database	USPAT; US-PGPUB; EPO; JPO	2004/05/12 11:00
-	1	("20030126109").PN.	USPAT; US-PGPUB; EPO; JPO	2004/05/10 10:36
-	15808	(transform$4 convert$4) with (message file text data string) with table	USPAT; US-PGPUB; EPO; JPO	2004/05/07 14:04
-	6014	user with defin$4 with (table format)	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:17
-	269	extract with message adj data	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:20
-	2	((transform$4 convert$4) with (message file text data string) with table) and (user with defin$4 with (table format)) and ((pars$4 with (message data file text string) with queue with table) (extract with message adj data) (table with insert with message adj data))	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:21
-	6	table with insert with message adj data	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:31
-	452	((transform$4 convert$4) with (message file text data string) with table) and (user with defin$4 with (table format))	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:38
-	22	pars$4 with (message data file text string) with queue with table	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:51
-	2203	707/102.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:54
-	1086	message with table with format	USPAT; US-PGPUB; EPO; JPO	2004/05/07 13:58
-	5	707/102.ccls. and (message with table with format)	USPAT; US-PGPUB; EPO; JPO	2004/05/07 14:04

-	2102	delimit$4 with character	USPAT; US-PGPUB; EPO; JPO	2004/05/07 14:06
-	244	delimit$4 with character same table	USPAT; US-PGPUB; EPO; JPO	2004/05/07 14:07
-	25	delimit$4 with character same table same (message queue)	USPAT; US-PGPUB; EPO; JPO	2004/05/07 14:07
-	1	("20020046248").PN.	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:42
-	14205	(read retrieve) with (remove erase devour)	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:43
-	253	(read retrieve) with (remove erase devour) and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:44
-	14	(read retrieve) with (remove erase devour) with message and 707/$.ccls.	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:48
-	926	check$4 with function same build$4 function with exist same register with function	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:50
-	0	check$4 with function same build$4 with function with exist same register with function	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:51
-	6	check$4 with function same build$4 with function same register with function	USPAT; US-PGPUB; EPO; JPO	2004/05/10 16:51
-	2766	(choose select set) with read with message	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:14
-	99	(choose select set) with read with message with (delete devour$4 remove copy)	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:21
-	6	(choose select set) with read with (transaction message) with (delete devour$4 remove copy) same database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:23
-	0	read with (remove dequeue) with (choos$4 choise select$4 decid$4) with message same database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:42
-	2261	(generat$4 build$4) with (code function) with exist	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:43
-	3	(generat$4 build$4) with (code function) with exist and register with generat$4 with database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:44
-	3	(generat$4 build$4) with (code function) with exist and register with (generat$4 buil$5) with database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 14:47
-	14	nam$4 with column with table and convert$4 with (string text) with (data type format) with column	USPAT; US-PGPUB; EPO; JPO	2004/05/12 09:50
-	66	dequeue with (decide choose select pick option)	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:05
-	8	dequeue with (decide choose select pick option) same read and database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:11
-	31	destructive with read with (choose select pick decide designate)	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:14

-		24	destructive near2 read with (choose select pick decide designate)	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:36
-		1	(build$4 generat$4) with pars$5 with function with database same exist	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:37
-		39	(build$4 generat$4) with pars$5 with function with database	USPAT; US-PGPUB; EPO; JPO	2004/05/11 16:38